





Millitec Food Systems
Innovation in Automation



SPC Conveyor Range

sandwich production conveyors



www.millitec.com



Millitec Food Systems

Innovation in Automation

Conveyor Range

clean reliable conveyors

Introduction

Millitec's SPC range of sandwich production conveyors represent the ultimate in efficient and hygienic sandwich production. They form the heart of an integrated production system and come complete with integration for:

- Bread denester
- Collator
- Butterer
- 2 off depositors
- On line slicers
- Automatic belt cleaner CIP
- Automatic ladder
- Cutting machine

The entire range is designed with hygiene in mind with sloping surfaces and smooth lines throughout. In-built pneumatic and IP65 sealed electrical distribution mean that your entire production line is fed from a single electrical and pneumatic supply leaving your production hall uncluttered from cables and pipes.

The system has an in built link to allow it to be directly collected to our INFORM production planning and monitoring system so that real time data can be shared between the offices and production hall.

Features

- Cantilever designs for quick and easy belt removal
- Food Quality centre tracked sealed belts
- Angled surfaces to minimise product build up
- In-built quick release belt scraper
- IP 65 electrical protection
- Variable speed and touch screen control
- Quick release belt tension and tracking memory
- 900mm \pm 50mm standard height
- Facility to be networked onto our production planning/monitoring systems
- Built in air and electrical distribution
- Rail system both sides allows the fitting of numerous accessories

All machines are available for free trial or rental.

Specifications

SPC Range

- Touch screen and PLC control
- In-built integration for collator, butterer, 2 depositors, slicer, CIP and cutter
- Variable speed from touch screen
- Scale sockets along full length of line
- Accessory support rails along entire line
- Centre tracked fully sealed anti-microbial belt
- White line on belt for product placement

Dimensions

- SPC 500: 500mm wide - belt widths up to 390mm
- SPC 700: 700mm wide - belt widths up to 590mm
- Length: 5000mm to 16000mm available

Electrical

- Voltage: 380-440V AC
- Current: 16A
- Frequency: 50-60Hz 3 Phase and neutral

Pneumatics (where applicable)

- 6bar pressure
- Air outlets along conveyor length to suit



Contact

Millitec Food Systems Ltd
Woodhill Industrial Park
Old Dalby
Leicestershire
LE14 3LX

